FLIGHT SUMMARY REPORT

Flight #:

91-097

Date:

5 June 1991

Sensor Package: Wild-Heerbrug RC-10 Airborne Ocean Color Imager (AOCI)

Area(s) Covered: Off-shore Washington

Investigator(s): Richardson, Florida International University

Aircraft #: 709

Flight Request: 91B285

Julian Date: 156

SENSOR DATA

Accession #:

04229

Sensor ID #:

033

090

Sensor Type:

RC-10

AOCI

Focal Length:

Film Type:

Aerial Color

153.17 mm

SO242

Filtration:

2.2 AV

Spectral Band:

400-700 nm

f Stop:

Shutter Speed:

1/75

of Frames:

59

% Overlap:

60

Quality:

Excellent

Good

Remarks:

No Channel 5

Airborne Science and Applications Program

The Airborne Science and Applications Program (ASAP) is supported by three ER-2 high altitude Earth Resources Survey aircraft. These aircraft are operated by the High Altitude Missions Branch at NASA-Ames Research Center, Moffett Field, California. The ER-2s are used as readily deployable high altitude sensor platforms to collect remote sensing and in situ data on earth resources, celestial phenomena, atmospheric dynamics, and oceanic processes. Additionally, these aircraft are used for electronic sensor research and development and satellite investigative support.

The ER-2s are flown from various deployment sites in support of scientific research sponsored by NASA and other federal, state, university, and industry investigators. Data are collected from deployment sites in Kansas, Texas, Virginia, Florida, and Alaska. Cooperative international scientific projects have deployed the aircraft to sites in Great Britain, Australia, Chile, and Norway.

Photographic and digital imaging sensors are flown aboard the ER-2s in support of research objectives defined by the sponsoring investigators. High resolution mapping cameras and digital multispectral imaging sensors are utilized in a variety of configurations in the ER-2s' four pressurized experiment compartments. The following provides a description of the digital multispectral sensor used for data collection during this flight.

Airborne Ocean Color Imager

The Airborne Ocean Color Imager (AOCI) is a high altitude multispectral scanner designed for oceanographic remote sensing. It provides 10-bit digitization of eight bands in the visible/near-infrared region of the spectrum, plus two 8-bit bands in the near and thermal infrared. The bandwidths are as follows:

| Channel | Wavelength, um |
|---------|----------------|
| 1 | 0.436 - 0.455 |
| 2 | 0.481 - 0.501 |
| 3 | 0.511 - 0.531 |
| 4 | 0.554 - 0.575 |
| 5 | 0.610 - 0.631 |
| 6 | 0.655 - 0.676 |
| 7 | 0.741 - 0.800 |
| 8 | 0.831 - 0.897 |
| 9 | 0.989 - 1.054 |
| 10 | 8.423 - 12.279 |

Sensor/aircraft parameters are as follows:

IFOV:

2.5 mrad

Ground Resolution:

163 feet (50 meters) at 65,000 feet

Total Scan Angle:

850

Swath Width:

19.6 nmi (36.3 km) at 65,000 feet

Pixels/Scan Line:

716

Scan Rate: Ground Speed

6.25 scans/second

Ground Speed: Digitization:

400 kts (206 m/second) 8-bit channels 9-10

10-bit channels 1-8

NOTE: Information on data tape format, logical record format, and scanner calibration data may be obtained from the NASA-Ames Aircraft Data Facility at (415) 604-6252 or FTS 464-6252.

CAMERA FLIGHT LINE DATA FLIGHT NO. 91-097

04229 Accession #

Sensor #


033

| Check | Frame | Time (GMT- | Time (GMT-hr, min, sec) | Altitude, MSL | |
|--------|-----------|------------|-------------------------|---|---|
| Points | Numbers | START | END | feet/meters | Cloud Cover/Remarks |
| A - B | 8740-8755 | 23:00:57 | 23:14:01 | 65000/19800 | 10-100% stratus (frames 8743-8755) |
| D - E | 8756-8769 | 23:32:40 | 23:43:30 | = | Clear |
| F - G | 8770-8784 | 23:48:44 | 24:00:50 | = | 10-50% stratus-cumulus (frames 8783-8784) |
| I - Н | 8785-8798 | 24:05:26 | 24:16:36 | z. | 10% stratus-cumulus (frames 8785-8786) |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | 4 | | |
| | | | | | |
| | | | | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, | |
| | | | | ě | |
| | | | | | |
| | | | 3 | | |

SCANNER FLIGHT LINE DATA FLIGHT NO. 91-097

| DATA | |
|----------------------|-------|
| FL IGHT | |
| DAEDALUS FLIGHT DATA | 11101 |

| | total Repeated scanlines | 12 | 18 | 9 | 18 |
|----------------------|--|-----------------------|-----------------------|-----------------------|-----------------------|
| | total total G o o d Interpolated scanlines scanlines | Ø | Ø | Ø | Ø |
| | total Good scanlines | 5001 | 92.01 | 46.01 | 4401 |
| | Scan Speed (rps) | 6.25 | 6.25 | 6.25 | 6.25 |
| LEATH NOTIBER 31-83/ | Altitude feet/meter | 65000/19812 | 65000/19812 | 65000/19812 | 65000/19812 |
| | Actual scanline egin end | 49560 | 60984 | 67198 | 73108 |
| | Actual scanline begin end | 44548 | 51766 60984 | 62584 | 68690 73108 |
| | Actual time (GMT) begin end | 23:00:21.0 23:13:43.0 | 23:19:36.Ø 23:44:11.Ø | 23:48:27.0 00:00:44.0 | BB:B4:44.B BB:16:31.B |
| | Check Points | A-B |) بر د د | 5 - - | - |



AOCI / RC-10 / LAC's

